tehnoteka

https://tehnoteka.rs

# Informacije o proizvodu (EN)

## BEKO side by side frižider GN163241XBN



Tehnoteka je online destinacija za upoređivanje cena i karakteristika bele tehnike, potrošačke elektronike i IT uređaja kod trgovinskih lanaca i internet prodavnica u Srbiji. Naša stranica vam omogućava da istražite najnovije informacije, detaljne karakteristike i konkurentne cene proizvoda.

Posetite nas i uživajte u ekskluzivnom iskustvu pametne kupovine klikom na link:

https://tehnoteka.rs/p/beko-side-by-side-frizider-gn163241xbn-akcija-cena/

# PRODUCT INFORMATION SHEET

| | | | |
|---|---|---|---|
| **Supplier's name or trade mark (b),(d) :** | Beko | | |
| **Supplier's address (b),(d) :** | Arctic S.A Gaesti, Dambovita, 13 Decembrie Street, No 210, Romania | | |
| Model identifier (d) : | GN163241XBN 7290341395 | | |
| Type of refrigerating appliance: | | | |
| Low-noise appliance: | NO | Design type: | Free-Standing |
| Wine storage appliance: | NO | Other refrigerating appliance: | YES |

General product parameters:

| Parameter | | Value | Parameter | Value |
|---|---|---|---|---|
| Overall dimensions (millimetre) | Height | 1790 | Total volume (dm³ or l) | 576 |
| | Width | 910 | Energy efficiency class | E |
| | Depth | 705 | Airborne acoustical noise emission class | C |
| EEI | | 100 | Climate class: | Extended temperate / Tropical |
| Airborne acoustical noise emissions (dB(A) re 1 pW) | | 38 | | |
| Annual energy consumption (kWh/a) | | 328 | | |
| Minimum ambient temperature (°C), for which the refrigerating appliance is suitable | | 10 | Maximum ambient temperature (°C), for which the refrigerating appliance is suitable | 43 |
| Winter setting | | NO | | |

Compartment Parameters:

| Compartment type | | Compartment parameters and values | | | |
|---|---|---|---|---|---|
| | | Compartment Volume (dm³ or l) | Recommended temperature setting for optimised food storage (°C) These settings shall not contradict the storage conditions set out in Annex IV, Table 3 | Freezing capacity (kg/24 h) | Defrosting type (auto-defrost=A, manual defrost=M) |
| Pantry | NO | - | - | - | - |
| Wine storage | NO | - | - | - | - |
| Cellar | NO | - | - | - | - |
| Fresh food | YES | 364,0 | 4 | - | A |
| Chill | NO | - | - | - | - |
| 0-star or ice- making | NO | - | - | - | - |
| 1-star | NO | - | - | - | - |
| 2-star | NO | - | - | - | - |
| 3-star | NO | - | - | - | - |
| 4-star | YES | 212,0 | -18 | 13,0 | A |
| 2-star section | NO | - | - | - | - |
| Variable temperature compartment | NO | - | - | - | - |

| | |
|---|---|
| For 4-star compartments | |
| Fast freeze facility | YES |
| **For wine storage appliances** | |
| **Number of standard wine bottles** | - |
| Light source parameters (a) (b): | |
| Type of light source | LED |
| Energy efficiency class | G |
| Minimum duration of the guarantee offered by the manufacturer (b),(d) : | 24 Months |
| Additional information (b),(d) : | |

**Weblink to the manufacturer's website, where the information in point 4(a) Annex of CommissionRegulation (EU) 2019/2019 (1) (b) is found:**

http://support.beko.com

( a ) as determined in accordance with Commission Delegated Regulation (EU) 2019/2015 (2 ). ( b ) changes to this item shall not be considered relevant for the purposes of point 4 of Article 4 of Regulation (EU) 2017/1369. ( d ) this item shall not be considered relevant for the purpose of Article 2(6) of Regulation (EU) 2017/1369.

# TECHNICAL DOCUMENTATION

A general description of the refrigerating model, sufficient for it to be unequivocally and easily identified:

| | |
|---|---|
| Brand name | Beko |
| Model identifier (d) : | GN163241XBN 7290341395 |

Product specifications:

General product specifications:

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| Annual energy consumption (kWh/a) | 328,14 | EEI (%) | 99,8 |
| Standard annual energy consumption (kWh/a) | 328,80 | Combi parameter | 1,49 |
| Temperature rise time (h) | 9,00 | Load factor | 1,0 |
| Door heat loss factor | 1,000 | Climate class: | Extended temperate / Tropical |
| Anti-condensation heater type | Ambient | Airborne acoustical noise emissions (dB(A) re 1 pW) | 38 |

Additional product specifications for refrigerating appliances, except for low noise refrigerating appliances:

| Parameter | Value |
|---|---|
| Daily energy consumption at 32 °C (kWh/24h) | 1,265 |

Additional product specifications for low noise refrigerating appliances:

| Parameter | Value |
|---|---|
| Daily energy consumption at 25 °C (kWh/24h) | - |

**Additional product specifications for wine storage appliances**

| **Parameter** | Value | **Parameter** | Value |
|---|---|---|---|
| Internal humidity (%) | - | Number of bottles | - |

Compartment specifications:

| | Compartment parameters and values | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Compartment type | Target temperature (°C) | Compartment Volume ($dm^3$ or l) | Freezing capacity (kg/24 h) | Thermodynamic parameter (rc) | Nc | Mc | Defrost factor (Ac) | Built-in factor (Bc) |
| Pantry | - | - | - | - | - | - | - | - |
| Wine storage | - | - | - | - | - | - | - | - |
| Cellar | - | - | - | - | - | - | - | - |
| Fresh food | 4 | 364,0 | - | 1,00 | 75 | 0,12 | 1,00 | 1,00 |
| Chill | - | - | - | - | - | - | - | - |
| 0-star or ice- making | - | - | - | - | - | - | - | - |
| 1-star | - | - | - | - | - | - | - | - |
| 2-star | - | - | - | - | - | - | - | - |
| 3-star | - | - | - | - | - | - | - | - |
| 4-star | -18 | 212,0 | 13,0 | 2,10 | 138 | 0,15 | 1,10 | 1,00 |
| 2-star section | - | - | - | - | - | - | - | - |
| Variable temperature compartment | - | - | - | - | - | - | - | - |
| The sum of the volumes of the chill compartment(s) and the unfrozen compartment(s) [l or dm3 ] | | 364 | | | | | | |
| The sum of the volumes of the frozen compartment(s) [l or dm3 ] | | 212 | | | | | | |

Additional information (b),(d) :

The references of the harmonised standards or other reliable accurate and reproducible methods applied: EN 62552-1:2020, EN 62552-2:2020, EN 62552-3:2020, EN60704-2-14:2019

## Calculations

### Annual energy consumption (kWh/a) , T average (°C) :

$$E_{\text{daily}} = P \times 24 + \frac{\Delta E_{df} \times 24}{\Delta t_{df}} \quad (2)$$

Where

$E_{\text{daily}}$ is the energy in Wh over a period of 24 h

24 is h/d

$P$ is the **steady state** power in watt for the selected **temperature control setting** as per Annex B.

$\Delta E_{df}$ is the representative incremental energy for **defrost and recovery** in Wh in accordance with Annex C (see C.5).

$\Delta t_{df}$ is the estimated **defrost interval** in hours in accordance with Annex D.

Where there are additional defrost systems (each with its own **defrost control cycle**), the value of term based on $\Delta E_{df}$ and $\Delta t_{df}$ is also added in Formula (2) for each additional defrost system.

$$T_{\text{average}} = T_{ss} + \frac{\Delta Th_{df}}{\Delta t_{df}} \quad (3)$$

Note : EN 60552-3:2020 , 6.8.2 clause, Equation 2-3 ,

### Annual Energy , Daily energy consumption at 16 °C/ 32°C (kWh/24h) :

$$AE = 365 \times E_{daily}/L + E_{aux} \qquad E_{daily} = 0,5 \times (E_{16} + E_{32})$$

Note : EN 60552-3:2020 , 6.8.2 clause, Equation 4,(EU) 2019/2019 Ecodesign Requirements Directive

### Standard annual energy consumption (kWh/a)

SAE, expressed in kWh/a and rounded to two decimal places, is calculated as follows:

$$SAE = C \times D \times \sum_{c=1}^{n} A_c \times B_c \times [V_c/V] \times (N_c + V \times r_c \times M_c)$$

The modelling parameters are set out in Table 4.

*Table 4*

**The values of the modelling parameters per compartment type**

| Compartment type | $r_c$ (a) | $N_c$ | $M_c$ | $C$ |
|---|---|---|---|---|
| Pantry | 0,35 | | | |
| Wine storage | 0,60 | 75 | 0,12 | between 1,15 and 1,56 for combi appliances with 3- or 4-star compartments (b), 1,15 for other combi appliances, 1,00 for other refrigerating appliances |
| Cellar | 0,60 | | | |
| Fresh food | 1,00 | | | |
| Chill | 1,10 | 138 | 0,12 | |
| 0-star & ice-making | 1,20 | 138 | 0,15 | |
| 1-star | 1,50 | | | |
| 2-star | 1,80 | | | |
| 3-star | 2,10 | | | |
| Freezer (4-star) | 2,10 | | | |

(a) $r_c = (T_a - T_c)/20$; with $T_a = 24$ °C and $T_c$ with values as set out in Table 3.

(b) $C$ for combi appliances with 3- or 4-star compartments is determined as follows:
where $frzf$ is the 3- or 4-star compartment volume $V_f$, as a fraction of V with $frzf = V_f/V$:
— if $frzf \leq 0,3$ then $C = 1,3 + 0,87 \times frzf$;
— else if $0,3 < frzf < 0,7$ then $C = 1,87 - 1,0275 \times frzf$;
— else $C = 1,15$.

The compensation factors are set out in Table 5.

*Table 5*

**The values of the compensation factors per compartment type**

| Compartment type | $A_c$ | | $B_c$ | | $D$ | | | |
|---|---|---|---|---|---|---|---|---|
| | Manual defrost | Auto-defrost | Freestanding appliance | Built-in appliance | ≤ 2 (*) | 3 (*) | 4 (*) | > 4 (*) |
| Pantry | 1,00 | | 1,00 | 1,02 | 1,00 | 1,02 | 1,035 | 1,05 |
| Wine storage | | | | | | | | |
| Cellar | | | | | | | | |
| Fresh food | | | | | | | | |
| Chill | | | | 1,03 | | | | |
| 0-star & ice-making | 1,00 | 1,10 | | 1,05 | | | | |
| 1-star | | | | | | | | |
| 2-star | | | | | | | | |
| 3-star | | | | | | | | |
| Freezer (4-star) | | | | | | | | |
| (*) number of external doors or compartments, whichever is lowest. | | | | | | | | |

Note : (EU) 2019/2019 Ecodesign Requirements Directive, Clause 5, Table 4-5

5. Determination of the EEI:

EEI, expressed in % and rounded to the first decimal place, calculated as:

EEI = AE/SAE.

Note : (EU) 2019/2019 Ecodesign Requirements Directive, Clause 5

Auxiliary energy (kWh/a)

$$W_{heaters} = \left[\sum_{i=1}^{k} (R_i \times P_{H\,i})\right] \times 1{,}3 \qquad (40)$$

**Table F.1 — Format for temperature and humidity data – Ambient controlled anti-condensation heaters**

| Relative Humidity | RH band mid-point | Probability $R_i$ at 16 °C | Probability $R_i$ at 22 °C | Probability $R_i$ at 32 °C | Heater W at 16 °C | Heater W at 22 °C | Heater W at 32 °C |
|---|---|---|---|---|---|---|---|
| 0 to 10 % | 5 % | 0,00 % | 0,00 % | 0,34 % | $P_{H1}$ | $P_{H11}$ | $P_{H21}$ |
| 10 to 20 % | 15 % | 0,61 % | 6,86 % | 2,01 % | $P_{H2}$ | $P_{H12}$ | $P_{H22}$ |
| 20 to 30 % | 25 % | 3,11 % | 14,57 % | 1,61 % | $P_{H3}$ | $P_{H13}$ | $P_{H23}$ |
| 30 to 40 % | 35 % | 5,03 % | 14,83 % | 0,86 % | $P_{H4}$ | $P_{H14}$ | $P_{H24}$ |
| 40 to 50 % | 45 % | 5,09 % | 11,67 % | 0,18 % | $P_{H5}$ | $P_{H15}$ | $P_{H25}$ |
| 50 to 60 % | 55 % | 4,67 % | 8,31 % | 0,01 % | $P_{H6}$ | $P_{H16}$ | $P_{H26}$ |
| 60 to 70 % | 65 % | 3,39 % | 5,54 % | 0,00 % | $P_{H7}$ | $P_{H17}$ | $P_{H27}$ |
| 70 to 80 % | 75 % | 3,17 % | 2,51 % | 0,00 % | $P_{H8}$ | $P_{H18}$ | $P_{H28}$ |
| 80 to 90 % | 85 % | 2,85 % | 0,66 % | 0,00 % | $P_{H9}$ | $P_{H19}$ | $P_{H29}$ |
| 90 to 100 % | 95 % | 2,05 % | 0,07 % | 0,00 % | $P_{H10}$ | $P_{H20}$ | $P_{H30}$ |

Incremental defrost and recovery energy consumption at 16 /32 °C (Wh)

$$\Delta E_{dfj} = (E_{end-F} - E_{start-D}) - \frac{(P_{SS-D} + P_{SS-F})}{2} \times (t_{end-F} - t_{start-D}) \quad (19)$$

$$\Delta E_{df} = \frac{\sum_{j=1}^{m} \Delta E_{dfj}}{m} \quad (22)$$

Note : EN 62552-3:2020 Annex C,Clause C.3.3, Equation 19-22

Defrost interval at 16 /32 °C (h)

for Compressor Run Time Defrost Controller

$$\Delta t_{df} = \frac{\Delta t_{rt} - \Delta t_{dr} - \Delta t_{dh}}{CRt_{SS}} + \Delta t_{dxy} \quad (26)$$

for Variable Defrost Controller

$$\Delta t_{df32} = \frac{\Delta t_{d-max} \times \Delta t_{d-min}}{[0{,}2 \times (\Delta t_{d-max} - \Delta t_{d-min}) + \Delta t_{d-min}]} \quad (27)$$

$$\Delta t_{df16} = 2 \times \Delta t_{df16}$$

Note : EN 62552-3:2020, Annex D, Equation 26-27

tehnoteka

https://tehnoteka.rs

Ovaj dokument je originalno proizveden i objavljen od strane proizvođača, brenda Beko, i preuzet je sa njihove zvanične stranice. S obzirom na ovu činjenicu, Tehnoteka ističe da ne preuzima odgovornost za tačnost, celovitost ili pouzdanost informacija, podataka, mišljenja, saveta ili izjava sadržanih u ovom dokumentu.

Napominjemo da Tehnoteka nema ovlašćenje da izvrši bilo kakve izmene ili dopune na ovom dokumentu, stoga nismo odgovorni za eventualne greške, propuste ili netačnosti koje se mogu naći unutar njega. Tehnoteka ne odgovara za štetu nanesenu korisnicima pri upotrebi netačnih podataka. Ukoliko imate dodatna pitanja o proizvodu, ljubazno vas molimo da kontaktirate direktno proizvođača kako biste dobili sve detaljne informacije.

Za najnovije informacije o ceni, dostupnim akcijama i tehničkim karakteristikama proizvoda koji se pominje u ovom dokumentu, molimo posetite našu stranicu klikom na sledeći link:

https://tehnoteka.rs/p/beko-side-by-side-frizider-gn163241xbn-akcija-cena/